

# HANDY YET RUGGED

## 3인치 모바일 프린터 SPP-R300



### 주요특징



#### 스마트한 현장 업무의 필수품

- iOS, 안드로이드, 윈도우 등의 스마트 기기와 호환 가능 (MFI 인증)
- 간편한 무선인쇄 지원 (WLAN, Bluetooth)
- 방수 및 방진 기능 (IP54 with protective case)



#### 우수한 프린팅 성능

- 영수증 인쇄 시 최고 80 mm/sec 인쇄속도
- Linerless 용지 인쇄 가능 (옵션)
- 온도센서 내장으로 저온인쇄 (-15°C) 지원



#### 사용자 중심의 디자인

- 카드리더 일체형 옵션 (MSR)
- 모드전환 기능 지원 (영수증-라벨 용지)
- 원터치 커버 오픈, 드롭인 방식의 손쉬운 용지 교체



3인치 모바일 프린터

# SPP-R300



## 제품사양

Print Characteristics	
Print Method	Direct Thermal
Print Speed	Up to 100 mm/sec (Receipt) / Up to 80 mm/sec (Linerless) / 12.5% pattern
Print Resolution	203 dpi
Print Width	Up to 72 mm
Sensor	Paper End: Reflective sensor / Paper Cover Open: Mechanical switch
Media Characteristics	
Media Type	Receipt and Label, Linerless (optional)
Media Width	80 mm
Media Roll Diameter	Up to 50 mm
Media Thickness	0.07 ± 0.003 mm
Supply Method	Easy Paper Loading
Physical Characteristics	
Dimensions (W x L x H)	110.0 x 162.0 x 58.3 mm (4.33 x 6.38 x 2.30 inch)
Weight	Including battery: 550 g (1.21 lbs.) / Including MSR: 565 g (1.25 lbs.) / Paper: 133 g (0.29 lbs.)
Battery	7.4 V Li-ion, 2,600 mAh, Rechargeable Charging time: Up to 4.0 hrs
Performance Characteristics	
Memory	64 Mbit SDRAM, 32 Mbit FlashROM
Interface	USB V1.1 FS
	Serial
	Bluetooth V3.0 + EDR
	WLAN 802.11 b/g - WEP40/104, WPA1/2(PSK, EAP)
Environment Characteristics	
Temperature	Operating: -15 ~ 50°C (5 ~ 122°F) / Storage: -30 ~ 70°C (-22 ~ 158°F)
Humidity	Operating: 10 ~ 80% RH
Sealing	IP54 (with protective case)
Drop Spec	1.5 m (5 ft.)
Software	
Emulation	BXL / POS
Driver	Windows Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver
SDK	iOS SDK, Android SDK, Windows SDK, Symbian SDK
Fonts / Graphics / Symbologies	
Character Size	Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24 KOR, CHN: 24 x 24
Characters Per Line	Font A: 48 Font B, C: 64 KOR, CHN: 24
Character Sets	Alphanumeric: 95 / Expanded Graphics: 128 x 33 page / International: 32
Graphics	Supporting user-defined fonts, graphics, formats, layouts, and logos
Barcode Symbologies	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E
	2D: Data Matrix, MaxiCode, PDF417, QR code
Accessories	
Standard	Belt Strap, Battery Pack, Battery Charger, Power Cord, Paper
Optional	Case, Protective Case, Shoulder Strap, Single Battery Cradle, Quad Battery Charger, Vehicle Charger, Serial/USB Cable, Cleaning Pen
Integrated Card Reader (optional)	
MSR	3 Track, DUKPT (optional), T-DES Certified (optional)

BR-SPP-R300-KR-APR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

# BIXOLON®

www.bixolon.com



### BIXOLON Co., Ltd.

경기도 성남시 분당구 판교역로241번길  
20 (삼평동) 7~8층 463-400

Tel (031) 218 5500

Fax (031) 218 5589

E-mail sales@bixolon.com

### BIXOLON America Inc.

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

### BIXOLON Europe GmbH

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de